

NOTARY PUBLIC IN AND FOR THE STATE OF TEXAS

DEVELOPMENT APPLICATION

City of Rockwall Planning and Zoning Department 385 S. Goliad Street Rockwall, Texas 75087

57	AFF	USE	ONLY	-

PLANNING & ZONING CASE NO.

<u>NOTE:</u> THE APPLICATION IS NOT CONSIDERED ACCEPTED BY THE CITY UNTIL THE PLANNING DIRECTOR AND CITY ENGINEER HAVE SIGNED BELOW.

DIRECTOR OF PLANNING:

CITY ENGINEER:

			CITY	ENGINEER.	10,100		
PLEASE CHECK THE	APPROPRIATE BOX BELOW TO IND	ICATE THE TYPE OF	DEVELOPMENT RE	QUEST [SELECT	ONLY ONE BOX	x]:	
☐ PRELIMINARY ☐ FINAL PLAT (\$3 ☐ REPLAT (\$300. ☐ AMENDING OR ☐ PLAT REINSTA SITE PLAN APPLI ☒ SITE PLAN (\$25	(\$100.00 + \$15.00 ACRE) 1 PLAT (\$200.00 + \$15.00 ACRE) 1 300.00 + \$20.00 ACRE) 1 00 + \$20.00 ACRE) 1 MINOR PLAT (\$150.00) TEMENT REQUEST (\$100.00)	PLAN (\$100.00)	☐ SPECIFIC U ☐ PD DEVELO OTHER APPLIC ☐ TREE REMO ☐ VARIANCE F NOTES: 1: IN DETERMINING 1 PER ACRE AMOUNT. 2: A \$1,000.00 FEE	ANGE (\$200.00 + SE PERMIT (\$200 PMENT PLANS (\$ CATION FEES:	0.00 + \$15.00 AC \$200.00 + \$15.00 AL EXCEPTIONS THE EXACT ACREAC LESS THAN ONE ACRE THE APPLICATION F	CRE) 1 & 2 D ACRE) 1 S (\$100.00) 2 GE WHEN MULTIPI E, ROUND UP TO C	ONE (1) ACRE. EQUEST THAT
PROPERTY INFO	ORMATION [PLEASE PRINT]						
ADDRES	SEC Corporate Cross	ing & Fit Spor	rt Life Blvd.				
SUBDIVISIO	Fit Sport Life Addition			LOT	6	BLOCK	В
GENERAL LOCATIO	N SEC Corporate Cross	ing & Fit Spo	rt Life Blvd.				
ZONING, SITE P	LAN AND PLATTING INFOR	MATION [PLEASE	PRINT]				
CURRENT ZONIN	G C-Commercial		CURRENT USE	Vacant L	ot		
PROPOSED ZONIN	G N/A		PROPOSED USE	Fueling S	station w/ C	-Store	
ACREAG	E 1.95	LOTS [CURRENT]	1	LOT	S [PROPOSED]	1	
REGARD TO ITS	D PLATS: BY CHECKING THIS BOX YOU APPROVAL PROCESS, AND FAILURE TO DENIAL OF YOUR CASE.						
OWNER/APPLIC	ANT/AGENT INFORMATION	PLEASE PRINT/CHE	CK THE PRIMARY COM	NTACT/ORIGINAL S	SIGNATURES ARE	REQUIRED]	
□ OWNER				Triangle E			
CONTACT PERSON	CONOR KEILTY		CONTACT PERSON	Kartavya (Kevin) Pat	tel	
ADDRESS	3104 E Camelback Road #2	2387	ADDRESS	1782 W. N	1cDermott	Dr.	
CITY, STATE & ZIP	Phoenix, AZ 85016		CITY, STATE & ZIP	Allen, TX	75013		
PHONE	480-856-8808		PHONE	469.331.8	566		
E-MAIL	CONORK@STRUCTURED	REA.COM	E-MAIL	kpatel@tri	angle-engi	r.com	
EFORE ME, THE UNDE	CATION [REQUIRED] RSIGNED AUTHORITY, ON THIS DAY PER ION ON THIS APPLICATION TO BE TRUE			S CONOR K	CEIU[OWNER]	THE UNDER	SIGNED, WHO
290 March NFORMATION CONTAINE UBMITTED IN CONJUNC	T I AM THE OWNER FOR THE PURPOSE OF TO COVER THE COST OF TO COVER THE COST OF 2024. BY SIGNING THIS ED WITHIN THIS APPLICATION TO THE P	THIS APPLICATION, HAS APPLICATION, I AGREE PUBLIC. THE CITY IS	BEEN PAID TO THE CIT THAT THE CITY OF RO ALSO AUTHORIZED AND CIATED OR IN RESPONSI	Y OF ROCKWALL OF DCKWALL (I.E. "CITS D PERMITTED TO E TO A REQUEST FO	THIS THE	11th CAND PERMITTI COPYRICHTED MATHONIC Vashingto S Dillard	DAY OF TO PROVIDED INFORMATION
	OWNER'S SIGNATURE	01	1	(Commission	1 No. 185	589







City of Rockwall Planning & Zoning Department 385 S. Goliad Street

Planning & Zoning Department 385 S. Goliad Street Rockwall, Texas 75087 (P): (972) 771-7745 (W): www.rockwall.com The City of Rockwall GIS maps are continually under development and therefore subject to change without notice. While we endeavor to provide timely and accurate information, we make no guarantees. The City of Rockwall makes no warranty, express or implied, including warranties of merchantability and fitness for a particular purpose. Use of the information is the sole responsibility of the user.










	BOUNDARY LINE D	ATA			BOUNE	DARY C	URVE DATA	
LINE NO.	BEARING	DISTANCE	CURVE NO.	RADIUS	LENGTH	DELTA	CHORD BEARING	CHORD DISTANCE
L1	N 44°45'06" E	42.43'	C1	542.50'	18.48'	1°57'07"	N 88°46'32" E	18.48'
L2	N 89°45'06" E	45.46'	C2	42.50'	25.17	33°55'38"	N 70°50'15" E	24.80'
L3	N 62°39'05" E	208.73'	C3	42.50'	21.64'	29°10'40"	N 68°27'40" E	21.41'
L4	S 30°31'32" E	471.96'	C4	530'	137.98'	14°55'00"	N 75°35'16" E	137.59'
L5	S 89°10'38" W	410.08'	C5	530'	50.67'	5°28'40"	N 65°23'26" E	50.65'
L6	S 89°10'38" W	331.30'	C6	110'	48.96'	25°30'11"	S 13°21'44" E	48.56'
L7	N 00°28'18" E	53.84'						
L8	N 00°17'15" W	5.72'						
L9	N 00°14'54" W	159.68'						
L10	S 00°36'39" E	149.65'						

109.77'

S 26°06'50" E

EXISTING TREE LEGEND




01 TREE PRES	SER\		
		SCA	LE 1"=30'-0
0	15	40	8

TREE SURVEY FIELD DATA


NO.	SIZE	SPECIES	PROTECTED/	REMARKS
	(" DIA)	(COMMON NAME)	UNPROTECTED	
4301	36	WILLOW	UNPROTECTED	TO REMAIN
4302	6	HACKBERRY	UNPROTECTED	TO REMAIN
4303	6	HACKBERRY	UNPROTECTED	TO REMAIN
4304	12	HACKBERRY	UNPROTECTED	TO REMAIN
4305	7	HACKBERRY	UNPROTECTED	TO REMAIN
4306	16	HACKBERRY	UNPROTECTED	TO REMAIN
4307	12	HACKBERRY	UNPROTECTED	TO REMAIN
4308	7	HACKBERRY	UNPROTECTED	TO REMAIN
4309	7	HACKBERRY	UNPROTECTED	TO REMAIN
4310	6	CEDAR	UNPROTECTED	TO BE REMOVED
4311	7	HACKBERRY	UNPROTECTED	TO REMAIN
4312	14	HACKBERRY	UNPROTECTED	TO REMAIN
4313	6	HACKBERRY	UNPROTECTED	TO REMAIN
4314	8	HACKBERRY	UNPROTECTED	TO REMAIN
4315	14	HACKBERRY	UNPROTECTED	TO REMAIN
4316	14	HACKBERRY	UNPROTECTED	TO REMAIN

EXISTING TREE NOTES

- 1. Existing trees to remain shall be protected during construction from tree structure damage and compaction of soil under and around dripline (canopy)
- 2. If any root structure is damaged during adjacent excavation/construction, notify the Architect immediately. It is recommended that a licensed Arborist be secured for the treatment of any possible tree wounds.
- 3. No disturbance of the soil greater than 4" shall be located closer to the tree trunk than 1/2 the distance of the drip line to the tree trunk. A minimum of 75% of the drip line and root zone shall be preserved at natural grade.
- 4. Any fine grading done within the critical root zones of the protected trees must be done with light machinery such as a bobcat or light tractor. No earth moving equipment with tracks is allowed within the critical root zone of the
- 5. Material Storage: No materials intended for use in construction or waste materials accumulated due to excavation or demolition shall be placed within the limits of the dripline of any tree.
- 6. Equipment Cleaning/Liquid Disposal: No equipment may be cleaned, toxic solutions, or other liquid chemicals shall be deposited within the limits of the dripline of a tree. This would include but not be limited to paint, oil, solvents, asphalt, concrete, mortar, primers, etc.
- 7. Tree Attachments: No signs, wires or other attachments, other than those of a protective nature shall be attached to any tree.
- 8. Vehicular Traffic: No vehicular and construction equipment traffic or parking is allowed within the limits of the dripline of trees.
- 9. Boring of Utilities: May be permitted under protected trees in certain circumstances. The minimum length of the bore shall be the width of the tree's canopy and shall be a minimum depth of forty-eight (48") inches.
- 10. Trenching: Any irrigation trenching which must be done within the critical root zone of a tree shall be dug by hand and enter the area in a radial manner.
- 11. Tree Flagging: All trees to be removed from the site shall be flagged by the Contractor with bright red vinyl tape (3" width) wrapped around the main trunk at a height of four (4') feet above grade. Flagging shall be approved by Landscape Architect prior to any tree removal. Contractor shall contact Landscape Architect with 72 hour notice to schedule on-site meeting.
- 12. Protective Fencing: All trees to remain, as noted on drawings, shall have protective fencing located at the tree's dripline. The protective fencing may be comprised of snow fencing, orange vinyl construction fencing, chain link fence or other similar fencing with a four (4') foot approximate height. The protective fencing will be located as indicated on the Tree Protection Detail(s).
- 13. Bark Protection: In situations where a tree remains in the immediate area of intended construction, the tree shall be protected by enclosing the entire circumference of the tree's trunk with lumber encircled with wire or other means that does not damage the tree. Refer to Tree Protection Detail(s).
- 14. Construction Pruning: In a case where a low hanging limb is broken during the course of construction, the Contractor shall notify the Landscape Architect immediately. In no instance shall the Contractor prune any portion of the damaged tree without the prior approval by the Landscape Architect.



VICINITY MAP





SEE NOTES

PROJECT CONTACT LIST					
ENGINEER TRIANGLE ENGINEERING LLC 1782 W. McDERMOTT DRIVE ALLEN, TEXAS 75013 CONTACT: KARTAVYA PATEL, P.E. PHONE: 469-331-8566	DEVELOPER SCHAFFER CONSTRUCTION 2601 NETWORK BLVD., SUITE 413 FRISCO, TEXAS 75034 ERIN MILLER PHONE:214-888-6923 EMAIL: emiller@schafferconst.com				
SURVEYOR TRAVERSE LAND SURVEYING 14200 MIDWAY ROAD, SUITE 130 DALLAS, TEXAS 75244 CONTACT: GRAYSON CEBALLOS PHONE: 469-784-9321	ARCHITECT THE DIMENSION GROUP 10755 SANDHILL RD. DALLAS, TEXAS 75238 SARAH RANDALL 214-343-9400				
OWNER STRUCTURED REA-ROCKWALL LAND LLC 3104 E CAMELBACK RD, STE 2387 PHOENIX, ARIZONA 85016 CONOR KEILTY PHONE:480-856-8808 EMAIL: conork@structuredrea.com					

TO PROJECT BOUNDARY





CROSSING CORPORATE ELEVEN

ISSUE: FOR APPROVAL 03.14.2023

SHEET NAME: LANDSCAPE PLAN

DATE: 03.14.2024

SHEET NUMBER:

<u> </u>	BOUNDARY LINE D	ATA			BOUNE	DARY C	URVE DATA	
LINE NO.	BEARING	DISTANCE	CURVE NO.	RADIUS	LENGTH	DELTA	CHORD BEARING	CHORD DISTANCE
L1	N 44°45'06" E	42.43'	C1	542.50'	18.48'	1°57'07"	N 88°46'32" E	18.48'
L2	N 89°45'06" E	45.46'	C2	42.50'	25.17	33°55'38"	N 70°50'15" E	24.80'
L3	N 62°39'05" E	208.73'	C3	42.50'	21.64'	29°10'40"	N 68°27'40" E	21.41'
L4	S 30°31'32" E	471.96'	C4	530'	137.98'	14°55'00"	N 75°35'16" E	137.59'
L5	S 89°10'38" W	410.08'	C5	530'	50.67'	5°28'40"	N 65°23'26" E	50.65'
L6	S 89°10'38" W	331.30'	C6	110'	48.96'	25°30'11"	S 13°21'44" E	48.56'
L7	N 00°28'18" E	53.84'						

5.72'

159.68'

149.65'

109.77'

N 00°17'15" W

N 00°14'54" W

S 00°36'39" E

S 26°06'50" E

L8

L10

L11

TREES		
TYPE	QTY	COMMON NAME

REES					
TYPE	QTY	COMMON NAME	BOTANICAL NAME	SIZE	REMARKS
CE	4	Cedar Elm	Ulmus crassifolia	4" cal.	B&B, 12' ht., 5' spread, 6' clear straight trunk
LO	6	Live Oak	Live Oak	4" cal.	container, 12' ht., 5' spread, 6' clear straight trunk
RO	7	Red Oak	Quercus shumardii	4" cal.	container, 12' ht., 5' spread, 6' clear straight trunk
СМ	11	Crepe Myrtle	Lagerstroema indica	2" cal.	container, 8' ht., 4' spread, tree form
RB	10	Red Bud	Cercis candidensis	2" cal.	container, 8' ht., 4' spread, tree form
SHRUBS					
TYPE	QTY	COMMON NAME	BOTANICAL NAME	SIZE	REMARKS
DWM	117	Dwarf Wax Myrtle	Myrica pusilla	7 gal.	container, 36" ht., 30" spread
NRS	29	Nellie R. Stevens	Ilex x 'Nellie R. Stevens'	7 gal.	container, 36" ht., 30" spread
GROUN	DCOVERS				
TYPE	QTY	COMMON NAME	BOTANICAL NAME	SIZE	REMARKS
		'419' Bermudagrass	Cynodon dactylon '419'		solid sod refer to notes



- 1. CONTRACTOR SHALL VERIFY ALL EXISTING AND PROPOSED SITE ELEMENTS AND NOTIFY ARCHITECT OF ANY DISCREPANCIES. SURVEY DATA OF EXISTING CONDITIONS WAS SUPPLIED BY OTHERS.
- CONTRACTOR SHALL LOCATE ALL EXISTING UNDERGROUND UTILITIES AND NOTIFY ARCHITECT OF ANY CONFLICTS. CONTRACTOR SHALL EXERCISE CAUTION WHEN WORKING IN THE VICINITY OF UNDERGROUND UTILITIES.
- 3. CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL REQUIRED LANDSCAPE AND IRRIGATION PERMITS.
- 4. CONTRACTOR TO PROVIDE A MINIMUM 2% SLOPE AWAY FROM ALL STRUCTURES.
- 5. ALL PLANTING BEDS AND LAWN AREAS TO BE SEPARATED BY STEEL EDGING. NO STEEL TO BE INSTALLED ADJACENT TO SIDEWALKS OR
- 6. ALL LANDSCAPE AREAS TO BE 100% IRRIGATED WITH AN UNDERGROUND AUTOMATIC IRRIGATION SYSTEM AND SHALL INCLUDE RAIN AND FREEZE SENSORS.
- 7. ALL LAWN AREAS TO BE SOLID SOD BERMUDAGRASS, UNLESS OTHERWISE NOTED ON THE DRAWINGS.

LANDSCAPE TABULATIONS: I-30 Overlay / Commercial zoning

SITE REQUIREMENTS (site area 84,936 s.f.) Requirements: 20% site area to be landscaped

12,741 s.f. (15%) 36,649 s.f. (43%)

FRONT YARD REQUIREMENTS Requirements: 50% of required landscape must be located in front yard

Required 30,744 s.f. (100+%) 6,371 s.f. (50%)

STREET REQUIREMENTS

(4) canopy trees

Requirements: (2) canopy tree, 4" cal. & (4) accent tree, 4' ht. per 100 l.f. of frontage. Perimeter screening (30" height berm and 30" ht. evergreen shrubs.)

FIT SPORT LIFE BLVD. (249 I.f.)

Required (5) canopy trees (5) canopy trees (10) accent trees (10) accent trees 30" ht. berm 30" ht. berm 30" ht. evergreen shrubs 30" ht. evergreen shrubs


CORPORATE CROSSING (262 I.f.) Required Provided (5) canopy trees

(5) canopy trees (11) accent trees (11) accent trees 30" ht. berm 30" ht. berm 30" ht. evergreen shrubs 30" ht. evergreen shrubs

PARKING LOT REQUIREMENTS (32 spaces) Requirements: (1) canopy tree, 4" cal. per 10 parking spaces

Required

(4) canopy trees




VICINITY MAP

GENERAL LAWN NOTES

- 1. FINE GRADE AREAS TO ACHIEVE FINAL CONTOURS INDICATED ON CIVIL
- 2. ADJUST CONTOURS TO ACHIEVE POSITIVE DRAINAGE AWAY FROM BUILDINGS. PROVIDE UNIFORM ROUNDING AT TOP AND BOTTOM OF SLOPES AND OTHER BREAKS IN GRADE. CORRECT IRREGULARITIES AND AREAS WHERE WATER MAY STAND.
- 3. ALL LAWN AREAS TO RECEIVE SOLID SOD SHALL BE LEFT IN A MAXIMUM OF 1" BELOW FINAL FINISH GRADE. CONTRACTOR TO COORDINATE OPERATIONS WITH ON-SITE CONSTRUCTION MANAGER.
- IMPORTED TOPSOIL SHALL BE NATURAL, FRIABLE SOIL FROM THE REGION, KNOWN AS BOTTOM AND SOIL, FREE FROM LUMPS, CLAY, TOXIC SUBSTANCES, ROOTS, DEBRIS, VEGETATION, STONES, CONTAINING NO SALT AND BLACK TO BROWN IN COLOR.
- ALL LAWN AREAS TO BE FINE GRADED, IRRIGATION TRENCHES COMPLETELY SETTLED, AND FINISH GRADE APPROVED BY THE OWNER'S CONSTRUCTION MANAGER OR ARCHITECT PRIOR TO INSTALLATION.
- 6. ALL ROCKS 3/4" DIAMETER AND LARGER, DIRT CLODS, STICKS, CONCRETE SPOILS, ETC. SHALL BE REMOVED PRIOR TO PLACING TOPSOIL AND ANY LAWN INSTALLATION
- 7. CONTRACTOR SHALL PROVIDE (1") ONE INCH OF IMPORTED TOPSOIL ON ALL AREAS TO RECEIVE LAWN.

SOLID SOD NOTES

- FINE GRADE AREAS TO ACHIEVE FINAL CONTOURS INDICATED. LEAVE AREAS TO RECEIVE TOPSOIL 3" BELOW FINAL DESIRED GRADE IN PLANTING AREAS AND 1" BELOW FINAL GRADE IN TURF
- ADJUST CONTOURS TO ACHIEVE POSITIVE DRAINAGE AWAY FROM BUILDINGS. PROVIDE UNIFORM ROUNDING AT TOP AND BOTTOM OF SLOPES AND OTHER BREAKS IN GRADE. CORRECT IRREGULARITIES AND AREAS WHERE WATER MAY STAND.
- 3. ALL LAWN AREAS TO RECEIVE SOLID SOD SHALL BE LEFT IN A MAXIMUM OF 1" BELOW FINAL FINISH GRADE. CONTRACTOR TO COORDINATE OPERATIONS WITH ON-SITE CONSTRUCTION
- 4. CONTRACTOR TO COORDINATE WITH ON-SITE CONSTRUCTION MANAGER FOR AVAILABILITY OF EXISTING TOPSOIL.
- 5. PLANT SOD BY HAND TO COVER INDICATED AREA COMPLETELY. INSURE EDGES OF SOD ARE TOUCHING. TOP DRESS JOINTS BY HAND WITH TOPSOIL TO FILL VOIDS.
- 6. ROLL GRASS AREAS TO ACHIEVE A SMOOTH, EVEN SURFACE, FREE FROM UNNATURAL UNDULATIONS.
- 7. WATER SOD THOROUGHLY AS SOD OPERATION PROGRESSES.
- 8. CONTRACTOR SHALL MAINTAIN ALL LAWN AREAS UNTIL FINAL ACCEPTANCE. THIS SHALL INCLUDE, BUT NOT LIMITED TO: MOWING, WATERING, WEEDING, CULTIVATING, CLEANING AND REPLACING DEAD OR BARE AREAS TO KEEP PLANTS IN A VIGOROUS, HEALTHY CONDITION.
- 9. CONTRACTOR SHALL GUARANTEE ESTABLISHMENT OF AN ACCEPTABLE TURF AREA AND SHALL PROVIDE REPLACEMENT FROM LOCAL SUPPLY IF NECESSARY.
- 10. IF INSTALLATION OCCURS BETWEEN SEPTEMBER 1 AND MARCH 1, ALL SOD AREAS TO BE OVER-SEEDED WITH WINTER RYEGRASS, AT A RATE OF (4) POUNDS PER ONE THOUSAND (1000) SQUARE FEET.



PROJECT CONTACT LIST					
ENGINEER TRIANGLE ENGINEERING LLC 1782 W. McDERMOTT DRIVE ALLEN, TEXAS 75013 CONTACT: KARTAVYA PATEL, P.E. PHONE: 469-331-8566	DEVELOPER SCHAFFER CONSTRUCTION 2601 NETWORK BLVD., SUITE 413 FRISCO, TEXAS 75034 ERIN MILLER PHONE:214-888-6923 EMAIL: emiller@schafferconst.com				
SURVEYOR TRAVERSE LAND SURVEYING 14200 MIDWAY ROAD, SUITE 130 DALLAS, TEXAS 75244 CONTACT: GRAYSON CEBALLOS PHONE: 469-784-9321	ARCHITECT THE DIMENSION GROUP 10755 SANDHILL RD. DALLAS, TEXAS 75238 SARAH RANDALL 214-343-9400				
OWNER STRUCTURED REA-ROCKWALL LAND LLC 3104 E CAMELBACK RD, STE 2387 PHOENIX, ARIZONA 85016 CONOR KEILTY PHONE:480-856-8808 EMAIL: conork@structuredrea.com					

STUDIO GREEN SPOT, INC. 1782 W. McDERMOTT DR. ALLEN, TEXAS 75013 (469) 369-4448 CHRIS@STUDIOGREENSPOT.COM

> ORPORATE VEN

SING

0

Ш

Ш

ISSUE: FOR APPROVAL 03.14.2024

DATE:

SHEET NAME: LANDSCAPE PLAN

SHEET NUMBER:

03.14.2024

PART 1 - GENERAL

1.1 REFERENCED DOCUMENTS

Refer to bidding requirements, special provisions, and schedules for additional requirements.

Work included: Furnish all supervision, labor, materials, services, equipment and appliances required to complete the work covered in conjunction with the landscaping covered in these specifications and landscaping plans, including:

- 1. Planting (trees, shrubs, and grass)
- 4. Water and Maintenance until final acceptance Guarantee
- American Standard for Nursery Stock published by American Association of Nurserymen: 27 October 1980, Edition; by American National Standards Institute, Inc. (Z60.1) – plant
- American Joint Committee on Horticultural Nomenclature: 1942 Edition of Standardized

- The Contractor shall, within ten (10) days following acceptance of bid, notify the Architect/Owner of the sources of plant materials and bed preparation required for the
- gravel, and crushed stone. Samples shall be approved by Architect before use on
- materials.
- Submit three representative samples of each variety of ornamental trees, shrubs, and groundcover plants for Architect's approval. When approved, tag, install, and maintain as
- File Certificates of Inspection of plant material by state, county, and federal authorities with Architect, if required.
- F. Soil Analysis: Provide sandy loam soil analysis if requested by the Architect.

JOB CONDITIONS

- General Contractor to complete the following punch list: Prior to Landscape Contractor initiating any portion of landscape installation, General Contractor shall leave planting bed areas three (3") inches below finish grade of sidewalks, drives and curbs as shown on the drawings. All lawn areas to receive solid sod shall be left one (1") inch below the finish grade of sidewalks, drives, and curbs. All construction debris shall be removed prior to Landscape Contractor beginning any work.
- General Contractor shall provide topsoil as described in Section 02200 Earthwork.
- Storage of materials and equipment at the job site will be at the risk of the Landscape Contractor. The Owner cannot be held responsible for theft or damage.

1.6 MAINTENANCE AND GUARANTEE

A. Maintenance:

- 1. The Landscape Contractor will be held responsible for the maintenance of all work from the time of planting until final acceptance by the Owner. No trees, shrubs, groundcover or grass will be accepted unless they show a healthy growth and
- satisfactory foliage conditions 2. Maintenance shall include watering of trees and plants, cultivation, weeding spraying, edging, pruning of trees, mowing of grass, cleaning up and all other work necessary
- 3. A written notice requesting final inspection and acceptance should be submitted to the Owner at least seven (7) days prior to completion. An on-site inspection by
- Owner and Landscape Contractor will be completed prior to written acceptance. 4. After final acceptance of installation, the Landscape Contractor will not be required to do any of the above listed work.

- 1. Trees shall be guaranteed for a twelve (12) month period after acceptance. Shrubs and groundcover shall be guaranteed for twelve (12) months. The Contractor shall replace all dead materials as soon as weather permits and upon notification of the Owner. Plants, including trees, which have partially died so that shape, size, or symmetry has been damaged, shall be considered subject to replacement. In such cases, the opinion of the Owner shall be final.
- a. Plants used for replacement shall be of the same size and kind as those originally planted and shall be planted as originally specified. All work, including materials, labor and equipment used in replacements, shall carry a twelve (12) month guarantee. Any damage, including ruts in lawn or bed areas, incurred as a result of making replacements shall be immediately
- b. At the direction of the Owner, plants may be replaced at the start of the next year's planting season. In such cases, dead plants shall be removed from the premises immediately.
- c. When plant replacements are made, plants, soil mix, fertilizer and mulch are to be utilized as originally specified and reinspected for full compliance with Contract requirements. All replacements are to be included under "Work" of

2. The Owner agrees that for the guarantee to be effective, he will water plants at least twice a week during dry periods and cultivate beds once a month after final

- 3. The above guarantee shall not apply where plants die after acceptance because of injury from storms, hail, freeze, insects, diseases, injury by humans, machines or
- 4. Acceptance for all landscape work shall be given after final inspection by the Owner provided the job is in a completed, undamaged condition, and there is a stand of grass in all lawn areas. At this time, the Owner will assume maintenance on the
- Repairs: Any necessary repairs under the Guarantee must be made within ten (10) days after receiving notice, weather permitting, and in the event the Landscape Contractor does not make repairs accordingly, the Owner, without further notice to Contractor, may provide materials and men to make such repairs at the expense of the Landscape

1.7 QUALITY ASSURANCE

- General: Comply with applicable Federal, State, County and Local regulations governing landscape materials and work
- Personnel: Employ only experienced personnel who are familiar with the required work. Provide full time supervision by a qualified foreman acceptable to Landscape Architect.
- Selection of Plant Material:
 - 1. Make contact with suppliers immediately upon obtaining notice of contract acceptance to select and book materials. Develop a program of maintenance (pruning and fertilization) which will insure the purchased materials will meet and/or exceed project
 - 2. Landscape Architect will provide a key identifying each tree location on site. Written verification will be required to document material selection, source and delivery 3. Owner and/or Architect shall inspect all plant materials when reasonable at place of
 - growth for compliance with requirements for genus, species, cultivar/variety, size and 4. Owner and/or Architect retains the right to further inspect all plant material upon arrival at the site and during installation for size and condition of root balls, limbs,
- branching habit, insects, injuries, and latent defects. 5. Owner and/or Architect may reject unsatisfactory or defective material at any time during the process of work. Remove rejected materials from the site immediately. Plants damaged in transit or at job site shall be rejected.

PRODUCT DELIVERY, STORAGE AND HANDLING

TREE PLANTING DETAIL

1. Balled and Burlapped (B&B) Plants: Dig and prepare shipment in a manner that will not damage roots, branches, shape, and future development. 2. Container Grown Plants: Deliver plants in rigid container to hold ball shape and

- - 1. Deliver packaged materials in sealed containers showing weight, analysis and name of manufacturer. Protect materials from deterioration during delivery and while stored
 - 2. Deliver only plant materials that can be planted in one day unless adequate storage and watering facilities are available on job site.
 - 3. Protect root balls by heeling in with sawdust or other approved moisture retaining
- material if not planted within 24 hours of delivery. 4. Protect plants during delivery to prevent damage to root balls or desiccation of leaves.
- Keep plants moist at all times. Cover all materials during transport. 5. Notify Architect of delivery schedule 72 hours in advance so plant material may be
- observed upon arrival at job site. Remove rejected plant material immediately from site.
- 7. To avoid damage or stress, do not lift, move, adjust to plumb, or otherwise manipulate plants by trunk or stems.


PART 2 - PRODUCTS


- A. General: Well-formed No. 1 grade or better nursery grown stock. Listed plant heights are from tops of root balls to nominal tops of plants. Plant spread refers to nominal outer width of the plant, not to the outer leaf tips. Plants will be individually approved by the Architect and his decision as to their acceptability shall be final.
- Quantities: The drawings and specifications are complimentary. Anything called for on one and not the other is as binding as if shown and called for on both. The plant schedule is an aid to bidders only. Confirm all quantities on plan.
- Quality and size: Plant materials shall conform to the size given on the plan, and shall be healthy, symmetrical, well-shaped, full branched, and well rooted. The plants shall be free from injurious insects, diseases, injuries to the bark or roots, broken branches, objectionable disfigurements, insect eggs and larvae and are to be of specimen quality.
- Approval: All plant materials shall be subject to the approval of the Owner. All plants which are found unsuitable in growth, or in any unhealthy, badly shaped, or undersized condition, will be rejected by the Landscape Architect, either before or after planting, and shall be removed at the expense of the Landscape Contractor and replaced with


acceptable plants as specified.

- Trees shall be healthy, full-branched, well-shaped and shall meet the trunk diameter and height requirements of the plant schedule. Balls shall be firm, neat, slightly tapered, and well wrapped in burlap. Any tree loose in the ball or with broken ball at time of planting will be rejected. Balls shall be ten (10") inched in diameter for each one (1") inch of trunk diameter, Measured six (6") inched above ball.
- Nomenclature conforms to the customary nursery usage: for clarification, the term "multi-trunk" defines a plant having three (3) or more trunks of nearly equal diameter.
- Pruning: All pruning of trees and shrubs, as directed by the Landscape Architect, shall be executed by the Landscape Contractor at no additional cost to the Owner.

A = ROW SPACING B = ON CENTER SPACING SPACE PLANTS IN A TRIANGULAR PATTERNAS SHOWN, SPACED EQUALLY FROM EACHOTHER AT SPACING INDICATED ON PLANT LIST. PLANT ROW SPACING 'D' ROW SPACING 'A' PLANTS/10SF 2" MULCH DOUBLE SHREDDED HARDWOOD MULCH IN BED PRIOR TO -PLANTING GROUNDCOVER/ANNUALS. \ PREPARE GROUNDCOVER RED BY TILLING ENTIRE BED-AREA. PROVIDE SOIL MIX SPECIFICATIONS







		\sim
	SHRUBS AND GROUNDCOVER REFER TO PLANS FOR PLANT T	YPES
	PREPARED SOIL MIX PER SPECIFICATIONS	
	MULCH PER SPECIFICATIONS	'\\.
	1/8" X 4" GREEN STEEL EDGING WITH STAKES	L'ALLA CO
The state of the s	1/2" MAXIMUM LAWN	W 237
	NOTE: NO STEEL EDGING TO BE INSTALLED ALONG SIDEWALKS	6"
STEEL EDGING DETAIL		05 SHRUB
NO	OT TO SCALE (00

GROUNDCOVER PLANTING DETAIL

NOT TO SCALE

PROJECT CONTACT LIST					
ENGINEER TRIANGLE ENGINEERING LLC 1782 W. McDERMOTT DRIVE ALLEN, TEXAS 75013 CONTACT: KARTAVYA PATEL, P.E. PHONE: 469-331-8566	DEVELOPER SCHAFFER CONSTRUCTION 2601 NETWORK BLVD., SUITE 413 FRISCO, TEXAS 75034 ERIN MILLER PHONE:214-888-6923 EMAIL: emiller@schafferconst.com				
SURVEYOR TRAVERSE LAND SURVEYING 14200 MIDWAY ROAD, SUITE 130 DALLAS, TEXAS 75244 CONTACT: GRAYSON CEBALLOS PHONE: 469-784-9321	ARCHITECT THE DIMENSION GROUP 10755 SANDHILL RD. DALLAS, TEXAS 75238 SARAH RANDALL 214-343-9400				
OWNER STRUCTURED REA-ROCKWALL LAND LLC 3104 E CAMELBACK RD, STE 2387 PHOENIX, ARIZONA 85016 CONOR KEILTY PHONE:480-856-8808 EMAIL: conork@structuredrea.com					

A. Sandy Loam:

2.2 SOIL PREPARATION MATERIALS


- 1. Friable, fertile, dark, loamy soil, free of clay lumps, subsoil, stones and other extraneous material and reasonably free of weeds and foreign grasses. Loam
- containing Dallasgrass or Nutgrass shall be rejected. Physical properties as follows:
 - Clay between 7-27 percent Silt – between 15-25 percent Sand – less than 52 percent
- 3. Organic matter shall be 3%-10% of total dry weight. 4. If requested, provide a certified soil analysis conducted by an approved soil testing laboratory verifying that sandy loam meets the above requirements.
- Organic Material: Compost with a mixture of 80% vegetative matter and 20% animal waste. Ingredients should be a mix of course and fine textured material.
- Premixed Bedding Soil as supplied by Vital Earth Resources, Gladewater, Texas; Professional Bedding Soil as supplied by Living Earth Technology, Dallas, Texas or Acid Gro Municipal Mix as supplied by Soil Building Systems, Dallas, Texas or approved equal.
- Sharp Sand: Sharp sand must be free of seeds, soil particles and weeds.
- Mulch: Double Shredded Hardwood Mulch, partially decomposed, dark brown. Living Earth Technologies or approved equal.
- Organic Fertilizer: Fertilaid, Sustane, or Green Sense or equal as recommended for required applications. Fertilizer shall be delivered to the site in original unopened containers, each bearing the manufacturer's guaranteed statement of analysis.
- Commercial Fertilizer: 10-20-10 or similar analysis. Nitrogen source to be a minimum 50% slow release organic Nitrogen (SCU or UF) with a minimum 8% sulphur and 4% iron,
- Peat: Commercial sphagnum peat moss or partially decomposed shredded pine bark or


2.3 MISCELLANEOUS MATERIALS

- A. Steel Edging: Shall be Ryerson "Estate Curbing", 1/8" x 4" with stakes 4' on center.
- B. Staking Material for Shade Trees:

other approved organic material.

- 1. Post: Studded T-Post, #1 Armco with anchor plate; 6'-0" length; paint green. 2. Wire: 12 gauge, single strand, galvanized wire. 3. Rubber hose: 2 ply, fiber reinforced hose, minimum ½ inch inside diameter. Color:
- C. Gravel: Washed native pea gravel, graded 1 in. to 1-1/2 in.
- Filter Fabric: Mirafi 140N by Celanese Fibers Marketing Company, available at Loftland Co., (214) 631-5250 or approved equal.





ISSUE:

SHEET NAME: LANDSCAPE SPECIFICATIONS

1.2 DESCRIPTION OF WORK

- 2. Bed preparation and fertilization Notification of sources
- 1.3 REFERENCE STANDARDS

 - Texas Association of Nurserymen, Grades and Standards.
- Hortis Third, 1976 Cornell University
- 1.4 NOTIFICATION OF SOURCES AND SUBMITTALS
- Samples: Provide representative quantities of sandy loam soil, mulch, bed mix material,
- Product Data: Submit complete product data and specifications on all other specified
- representative samples for final installed plant materials.

PART 3 - EXECUTION

3.1 BED PREPARATION & FERTILIZATION

- Landscape Contractor to inspect all existing conditions and report any deficiencies to the
- B. All planting areas shall be conditioned as follows:
- Prepare new planting beds by scraping away existing grass and weeds as necessary. Till existing soil to a depth of six (6") inches prior to placing compost and fertilizer. Apply fertilizer as per manufacturers recommendations. Add six (6") inches of compost and till into a depth of six (6") inches of the topsoil. Apply organic fertilizer
- such as Sustane or Green Sense at the rate of twenty (20) pounds per one thousand (1,000) square feet. 2. All planting areas shall receive a two (2") inch layer of specified mulch. 3. Backfill for tree pits shall be as follows: Use existing top soil on site (use imported topsoil as needed) free from large clumps, rocks, debris, caliche, subsoils, etc.,
- placed in nine (9") inch layers and watered in thoroughly.
- C. Grass Areas: 1. Areas to be Solid Sod Bermudagrass: Blocks of sod should be laid joint to joint, (staggered joints) after fertilizing the ground first. Roll grass areas to achieve a
- smooth, even surface. The joints between the blocks of sod should be filled with topsoil where they are evidently gaped open, then watered thoroughly. 2. Areas to be Hydromulch Common Bermudagrass: Hydromulch with bermudagrass seed at a rate of two (2) pounds per one thousand (1,000) square feet. Use a 4' x 8'

batter board against the bed areas.

- Plant materials shall be delivered to the site only after the beds are prepared and area of earth of B & B plants shall be kept covered with soil or other acceptable material. All

3.2 INSTALLATION

- Maintenance of plant materials shall begin immediately after each plant is delivered to the
- ready for planting. All shipments of nursery materials shall be thoroughly protected from the drying winds during transit. All plants which cannot be planted at once, after delivery to the site, shall be well protected against the possibility of drying by wind and sun. Balls
- Position the trees and shrubs in their intended location as per plan. Notify the Landscape Architect for inspection and approval of all positioning of plant
- plants remain the property of the Contractor until final acceptance.
- site and shall continue until all construction has been satisfactorily accomplished.
- materials. Excavate pits with vertical sides and horizontal bottom. Tree pits shall be large enough to permit handling and planting without injury to balls of earth or roots and shall be of such depth that, when planted and settled, the crown of the plant shall bear the same

relationship to the finish grade as it did to soil surface in original place of growth.

- Shrub and tree pits shall be no less than two (2') feet, twenty-four (24") inches, wider than the lateral dimension of earth ball and six (6") inches deeper than it's vertical dimension. Remove and haul from site all rocks and stones over one (1") inch in diameter. Plants should be thoroughly moist before removing containers.
- Dig a wide, rough sided hole exactly the same depth as the height of the ball, especially at the surface of the ground. The sides of the hole should be rough and jagged, never slick Percolation Test: Fill the hole with water. If the water level does not percolate within 24
- hours, the tree needs to move to another location or have drainage added. Install a PVC stand pipe per tree planting detail as approved by the Landscape Archited Backfill only with 5 parts existing soil or sandy loam and 1 part bed preparation. When the hole is dug in solid rock, topsoil from the same area should not be used. Carefully settle by watering to prevent air pockets. Remove the burlap from the top 1/3 of the ball,
- as well as all nylon, plastic string and wire mesh. Container trees will usually be pot bound, if so follow standard nursery practice of 'root scoring'.
- Do not wrap trees.
- Do not over prune. Mulch the top of the ball. Do not plant grass all the way to the trunk of the tree. Leave the
- area above the top of the ball and mulch with at least two (2") inches of specified mulch. All plant beds and trees to be mulched with a minimum settled thickness of two (2")
- inches over the entire bed or pit Obstruction below ground: In the event that rock, or underground construction work or obstructions are encountered in any plant pit excavation work to be done under this section, alternate locations may be selected by the Owner. Where locations cannot be changed, the obstructions shall be removed to a depth of not less than three (3') feet below grade and no less than six (6") inches below the bottom of ball when plant is properly set at the required grade. The work of this section shall include the removal from
- the site of such rock or underground obstructions encountered at the cost of the Landscape Contractor.

secure tree against seasonal prevailing winds.

Pruning shall be done with clean, sharp tools.

Pruning and Mulching: Pruning shall be directed by the Architect and shall be pruned in accordance with standard horticultural practice following Fine Pruning, Class I pruning

Trees and large shrubs shall be staked as site conditions require. Position stakes to

- standards provided by National Arborist Association. 1. Dead wood or suckers and broken badly bruised branches shall be removed. General tipping of the branched is not permitted. Do not cut terminal branches.
 - a layer of organic material two (2") inches in depth. This limit of the organic material Steel Curbing Installation: 1. Curbing shall be aligned as indicated on plans. Stake out limits of steel curbing and

1. Stakes are to be installed on the planting bed side of the curbing, as opposed to the


3. Immediately after planting operations are completed, all tree pits shall be covered with

obtain Owners approval prior to installation. 2. All steel curbing shall be free of kinks and abrupt bends. . Top of curbing shall be 3/4" maximum height above grade

2. Do not install steel edging along sidewalks. 3. Cut steel edging at 45 degree angle where edging meets sidewalk.

3.3 CLEANUP AND ACCEPTANCE Cleanup: During the work, the premises shall be kept neat and orderly at all times. Storage areas for all materials shall be so organized that they, too, are neat and orderly. All trash and debris shall be removed from the site as work progresses. Keep paved

areas clean by sweeping or hosing at end of each days work. END OF SECTION



NOT TO SCALE

FOR APPROVAL 03.14.2024

STUDIO GREEN SPOT, INC

1782 W. McDERMOTT DR.

ALLEN, TEXAS 75013

(469) 369-4448

CHRIS@STUDIOGREENSPOT.COM

NS

OS

S

0

0

VEN

Щ

Ш

BLVI

DATE: 03.14.2024

SHEET NUMBER:

